

aspire for more...

Aspiria

CERAMIC

Decora Series

DIGITAL

Rustic Series

PORCELAIN

Glossy Series

TILES

Wood Series

600x600mm

600x1200mm


Punch Series



RL_GH_1001

WHITE BODY(GVT TILES)


600x600mm



RL_GH_1002

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1005

WHITE BODY(GVT TILES)


600x600mm



RL_GH_1006

WHITE BODY(GVT TILES)



600x600mm




RL_GH_1008

WHITE BODY(GVT TILES)

600x600mm






RL_GH_1010

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1012

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1013

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1015

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1016

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1017

WHITE BODY(GVT TILES)


600x600mm



RL_GH_1018

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1019

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1021

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1022

WHITE BODY(GVT TILES)


600x600mm



RL_GH_1024

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1027

WHITE BODY(GVT TILES)


600x600mm



RL_GH_1034

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1035

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1036

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1037

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1038

WHITE BODY(GVT TILES)

600x600mm



RL_GH_1039

WHITE BODY(GVT TILES)


600x600mm



RL_GH_1041

WHITE BODY(GVT TILES)

600x600mm





Particulars	Standard as per ISO 13006/EN 176	OUR VALUE	METHOD OF TESTING
Deviation in length	± 0.50%	± 0.3%	EN 98
Deviation in Thickness	± 5%	±3%	EN 98
Straightness Of Sides	± 0.5%	± 0.3%	EN 98
Rectangularity	± 0.6%	± 0.3%	EN 98
Surface Flatness	± 0.5%	± 0.3%	EN 98
Water Absorption	< 3	3 < 4	ISO 10945.3 EN 98
Mohs Hardness	> 5	> 5	EN 101
Flexural Strength	> 35 N/Sq.mm	> 39 N/Sq.mm	—
Abrasion Resistance	As specified by Manufacturer	PE 3	ISO 10545.6 EN 102
Frost Resistance	Frost Proof	Frost Proof	ISO 10534 - 11
Chemical Resistance	No Damage	No Damage	ISO 10534 - 18
Thermal Shock Resistance	No Damage	No Damage	ISO 10545- 9
Colour Resistance	No Damage	No Damage	—
Stain Resistance	Resistance	Stain Proof	ISO 10545 - 14
Moisture Expansion	Nill	Nill	ISO 10545 - 10
Crazing Resistance	Min 2 Cycle	Min 4 Cycle	—

Note :
Colour shown are as accurate as the limitations of the printing process will allow. Prospective customers are advised to inspect a sample of the tile before ordering. Every effort has been made to ensure the accuracy of the information given. However, the company reserves the right to change the specification without prior notice. Sometimes variations in shade or size being inherent to ceramic industry may occur. It is suggest to check the tiles before purchase and laying as the company dose not accept responsibility once the tiles are laid.

PACKING DETAIL				
Size	Thickness	No.OF Tiles	Area Approx.	Weight Approx.
600x600 mm	9 mm	4 Pcs.	1.44 Sq. Mtr.	28kg.



Airport



Shopping Center



Industries



Hospital



Schools



Hotel



Domestic



Offices



Super Markets



Restaurant – Cafee



Gym



Discotheques



Corridors



Religious Places



THANK YOU